

# Nanosecond Pulse Frequency Effects of Dielectric Barrier Discharge Plasma Actuator for Flow Separation Control over a NACA 0012 Airfoil


Kun Tang<sup>1</sup>, Xin Zhang<sup>1</sup>, Cheng Qin<sup>1</sup>, Kwing so Choi<sup>2</sup>, Longfei Song<sup>2</sup>

<sup>1</sup>China Aerodynamics Research and Development Center, China  
E-mail: tangkunjill@163.com,

<sup>2</sup>Faculty of Engineering, University of Nottingham, Nottingham, UK, NG7 2RD

**Keywords:** Separation control, nanosecond pulse , frequency.

High voltage pulsed nanosecond discharge can be an efficient tool for flow separation control of airfoil[1-9]. This work presents results of an experimental investigation of flow control using repetitive, high-voltage nanosecond dielectric barrier discharge(NS-DBD) plasma actuation on a NACA0012 airfoil. The control of separation flow at various Reynolds numbers lying between  $5 \times 10^5$  and  $1 \times 10^6$  was investigated using time-averaged pressure measurements, smoke-wire imagery visualizations and time-resolved particle image velocimetry(PIV) results. Here, an actuator was mounted at a distance from leading edge of 1% of the chord length. The measurement results of time-averaged pressure, which was selected as the index of separation control, indicate that the optimal driving frequency varies with the angle of attack. Several flow fields are discussed in detail in this paper. The smoke-wire imagery visualizations results indicate that a series of vortex structures, the produce frequency of which increase with increasing driving frequency in the experimental range, is shed from the shear layer for each driving actuation. The smoke-wire imagery visualizations and PIV measurements reveal that when Reynolds number is above  $1 \times 10^5$ , a driving frequency from  $F^+ = 1$  to  $F^+ = 5$  is able to promote turbulent transition and control the separation over the airfoil, whereas near the stall angle, the promotion of the turbulent transition provides better separation control. For lower Reynolds number for example  $5 \times 10^5$ , only when  $F^+$  is greater than or equal to 15 was the separation eventually controlled. It is also found that the transition from laminar to turbulence can be promoted by plasma actuation, and that flow transition acts as an important factor in the flow-separation control. At the beginning of the actuation, each actuation can produce a spanwise vortex around the separation point near the leading edge. The spanwise vortices make the separated free-shear unstable and shedding away, move downstream along the upper wall, and bring outer flow with high kinetic energy into the near wall region to change the flow structures over the airfoil. At last, the flow on the upper surface of the airfoil become fully attached.



(d)t=0.194s

(e)t=0.208s

(f)t=0.333s

Figure 1: Smoke visualization of interaction between flow and nanosecond pulses actuation.

.....

#### *Acknowledgements*

This study was supported by the Exploration Foundation of Weapon Systems (No. 7130711).

#### *References*

- [1] Chris C, Achal S and Mo S 2016 Flow control over an airfoil in fully reversed condition using plasma actuators *AIAA Journal*. **54** 141–149
- [2] Hai D, Zhiwei S and Keming C 2016 Frequency optimization and vortex dynamic process analysis of separated flow control by nanosecond pulsed plasma discharge *Acta Aeronautica et Astronautica Sinica*. **37** 2102–2111
- [3] Kato K, Breitsamter C and Obi S 2014 Flow separation control over an Go387 airfoil by nanosecond pulse-periodic discharge *Experiments in Fluids*. **55** 1–19
- [4] Rethmel C, Little J, Takashima K, et al. 2011 Flow separation control over an airfoil with nanosecond pulse driven DBD plasma actuators *49th AIAA Aerospace Sciences Meeting including the New Horizons Forum and Aerospace Exposition*
- [5] Rethmel C, Little J, Takashima K, et al. 2012 Separation control with nanosecond-pulse-driven dielectric barrier discharge plasma actuators *AIAA Journal*. **50** 350–365
- [6] I V Adamovich, S B Leonov, K Frederickson 2017 Thermal perturbations generated by near-surface electric discharges and mechanisms of their interaction with the airflow *55th AIAA Aerospace Sciences Meeting*
- [7] Correale G, Michelis T, Kotsonis M 2014 NS-DBD plasma actuation on a backward facing step *52nd Aerospace Sciences Meeting*
- [8] K D Bayoda, N Bernard and E Moreau 2015 Single nanosecond dielectric barrier discharge and pulsed sliding discharge applied to flow separation control along a NACA0015 airfoil *46th AIAA Plasmadynamics and Lasers Conference*
- [9] E Moreau, A Debien, N Benerd and N Zouzou 2016 Nanosecond-pulsed dielectric barrier discharge plasma actuator for airflow control along an NACA0015 airfoil at high Reynolds number *IEEE Transactions on Plasma Science*. **44** 2803–2811