

Assessment of simple Dielectric Barrier Discharge actuator model with a commercial flow solver

Yacine Babou¹, Pablo Lechuga², Rauno Cavallaro¹

¹Departamento de Bioingeniería Ingeniería Aeroespacial, Universidad Carlos III de Madrid Avenida de la Universidad 30, 28911, Leganes, Madrid, Spain

E-mail: ybabou@ing.uc3m.es, rauno.cavallaro@uc3m.es

² BS candidate at Departamento de Bioingeniería Ingeniería Aeroespacial, Universidad Carlos III de Madrid

Keywords: Electrohydrodynamic body force, plasma actuator, plasma flow control, von Karman instability.

The present contribution addresses a simplified expression of the distribution of the Electro-Hydrodynamic (EHD) force generated by a single Radio-Frequency (RF) Dielectric Barrier Discharge (DBD) plasma actuator. By combining judiciously different models previously documented, an upgraded EHD body force model has been elaborated in order to get an expression depending exclusively on the plasma actuator design and operating settings which can be effortlessly implemented as a source term in commercial flow solvers. We consider first the model established by Soloviev [1] to estimate the integral force produced per unit length of the exposed electrode. In order to apply this model as body force source term in commercial flow solver, the integral force is distributed leaning on the model proposed by Sing et al. [2].

The performance of the resulting model is assessed through a series of flow computations addressing several arrangements involving multiple actuators and documented in the literature; namely, the case of in-series actuator configuration [3], the case of flipped actuator configuration [4] and the case of actuated cylinder [5]. Comparisons between computed data and available flow measurements demonstrate the relevancy of the adopted modelling approach to predict flow actuation by means of conventional RF-DBD plasma actuator.




Figure 1: Flow behind a cylinder: $V'(t)$ evolution with actuators ON and OFF at point P3.

.....

Acknowledgements

This project has received funding from the Universidad Carlos III de Madrid, the European Union's Seventh Framework Programme for research, technological development and demonstration under grant agreement No600371, el Ministerio de Economía, Industria y Competitividad (COFUND2013-40258), el Ministerio de Educación, cultura y Deporte (CEI-15-17) and Banco Santander.

References

- [1] V. Soloviev, "Analytical estimation of the thrust generated by a surface dielectric barrier discharge," *Journal of Physics D: Applied Physics*, vol. 45, no. 2, p. 025205, 2011.
- [2] K. P. Singh and S. Roy, "Force approximation for a plasma actuator operating in atmospheric air," *Journal of Applied Physics*, vol. 103, no. 1, p. 013305, 2008.
- [3] E. Moreau, A. Debien, N. Bénard, T. Jukes, R. Whalley, K. Choi, A. Berendt, J. Podlinski, and J. Mizeraczyk, "Surface dielectric barrier discharge plasma actuators," *ERCOFTAC Bull*, vol. 94, no. 5, 2013.
- [4] M. Bolitho and J. Jacob, "Thrust vectoring flow control using plasma synthetic jet actuators," in *46th AIAA Aerospace Sciences Meeting and Exhibit*, p. 1368, 2008.
- [5] Barbato, Luigi. "Flow control using DBD plasma actuators: experimental investigation." Master thesis, von Karman Institute, 2011.