

TECHNOLOGICAL UNIVERSITY DELFT

DEPARTMENT OF AERONAUTICAL ENGINEERING

Report VTH-124

THEORETICAL AND EXPERIMENTAL INVESTIGATIONS
OF INCOMPRESSIBLE LAMINAR BOUNDARY LAYERS
WITH AND WITHOUT SUCTION

Ph.D THESIS

J.L. van INGEN

DELFT
the NETHERLANDS

OCTOBER, 1965

This PDF-file contains:

Summary, contents and list of symbols

Summary.

In this dissertation the results are presented of some theoretical and experimental investigations of two-dimensional laminar boundary layers with and without suction. Throughout the work the velocities involved are assumed to be of such a small magnitude that the effects of compressibility can be neglected. The investigations were undertaken with the purpose to clarify some points concerned with maintaining laminar flow in a boundary layer by means of suction through a porous surface. In the course of this work several results were obtained which also may be of interest for laminar boundary layers without suction. A first investigation is concerned with the calculation of laminar boundary layers by means of approximate methods of the type introduced by Pohlhausen. A new method is described which, by a special choice of the velocity profile, is capable of providing accurate results in those cases where the suction velocity is not too large.

The second theoretical investigation deals with a "phase plane" description of the laminar boundary layer flow between non-parallel plane walls. Here shear τ is plotted versus the velocity component u parallel to the wall.

This is analogous to the use of the phase plane method in the theory of non-linear oscillations with one degree of freedom where speed is plotted versus displacement. In the latter theory singular points in the phase-plane correspond to equilibrium positions of the oscillation. For the flow between non-parallel plane walls the singularities in the "phase plane" are shown to correspond to the edge of a boundary layer. It is shown that the occurrence of boundary layer type solutions depends on the character of the singularity which is determined by the amount of suction.

For the case of inflow between converging walls without suction τ^2 can be expressed as a polynomial in u . From this observation a new calculation method for laminar boundary layers evolves which is described in detail. The method assumes for τ^2 a polynomial expression in u with coefficients depending on the streamwise coordinate x . These coefficients are determined from compatibility conditions and from moments of a modified form of Crocco's boundary layer equation. In contrast to existing

approximate methods the new approach allows the degree N of the polynomial to be increased without unduly complicating the method. For increasing N the results of the approximate method seem to converge to the exact solution.

The experimental part of the work consists of measurements on two airfoil sections in a low speed wind tunnel. The first model is a 28^o/o thick laminar flow airfoil section with an impermeable surface and a chord length of 1 meter. A detailed survey of the velocity profiles in the laminar boundary layer was made with hot wires; the measurements were extended so far downstream as to include the laminar separation point. Results of the measurements and a comparison with laminar boundary layer theory are presented.

The second model is a 15^o/o thick, 1.35 meter chord, laminar flow wing section with porous upper- and lower surfaces between the 30^o/o and 90^o/o chord positions. The inside of the model is divided into 40 different compartments each with its own suction line, flow-regulating valve and -measuring device. Hence the chordwise suction distribution could be varied between wide limits. Wake drag and transition position were measured for several suction distributions; for some of these detailed boundary layer surveys were made. In one case the suction distribution was chosen in such a way that a separating laminar boundary layer was obtained.

From the transition measurements on the porous model a semi-empirical method is derived which permits the determination of the transition position for two-dimensional incompressible laminar boundary layers with arbitrary pressure- and suction distributions. This method is an extension of an existing method which was shown to be valid for the no-suction case both by Smith and Gamberoni [1,2] and the present author [3,4,5].

The boundary layer calculation methods and the transition criterion provide the means for a rational design of the suction distribution needed to maintain laminar flow for a given pressure distribution. For instance a suction distribution may be determined for which the total drag coefficient is as small as possible.

<u>Contents</u>	page
List of symbols	X
1. Introduction and outline of thesis	1
1.1. Introduction	1
1.2. Outline of thesis	2
2. The equations for two-dimensional laminar boundary layer flows	9
2.1. The Navier-Stokes equations	9
2.2. Prandtl's boundary layer equations	10
2.3. Compatibility conditions of the boundary layer equations	12
2.4. Moments of the boundary layer equations	12
3. Some known methods to obtain accurate solutions of the boundary layer equations	15
3.1. Similar solutions	15
3.1.1. General	15
3.1.2. Hartree's boundary layer flows for $U = u_1 x^{m_1}$	16
3.1.3. Blasius' solution for the flat plate without suction	18
3.1.4. The plane stagnation point without suction	19
3.1.5. The asymptotic suction boundary layer	19
3.2. Solutions in series	20
3.2.1. General	20
3.2.2. Blasius' series	20
3.2.3. Series solution from a cusped leading-edge	21
3.2.4. Görtler's series method	22
3.2.5. Disadvantages of the series methods	24
3.3. Finite difference methods	25
4. Approximate boundary layer calculations using moment equations and compatibility conditions	26
4.1. General	26
4.2. Pohlhausen's method	26
4.3. Other methods using the momentum equation and compatibility conditions	28

	page
4.4. Methods using the kinetic energy equation in addition to the momentum equation	30
4.5. Possible methods using moment equations of higher order	31
5. A new approximate method using the momentum equation for the calculation of boundary layers with and without suction	33
5.1. Introductory remarks	33
5.2. The expression for the velocity profile and related parameters	33
5.3. The momentum equation and compatibility conditions	35
5.4. Similar solutions	36
5.4.1. General	36
5.4.2. The similar boundary layers for $\bar{U} = u_1 \bar{x}^{\frac{m}{1}}$ without suction	38
5.4.3. The plane stagnation point flow with suction	39
5.4.4. The flat plate with $v_0 \propto x^{-\frac{1}{2}}$	39
5.5. Step by step calculation of the boundary layer starting from given initial conditions	39
5.6. Determination of the starting value for $\bar{\theta}$	42
5.7. Simplification of the method for the no-suction case	43
5.8. Determination of the best values for a and b	44
5.8.1. Determination of b	44
5.8.2. Determination of a	45
6. Phaseplane description of the boundary layer flow between non-parallel plane walls	46
6.1. Introductory remarks	46
6.2. The boundary layer equations for the flow between non-parallel plane-walls	48
6.3. The non-porous walls ($\lambda = 0$)	50
6.4. The effects of suction and blowing ($\lambda \neq 0$)	52
6.5. Consequences of some results of the phase plane description for practical boundary layer calculations	56

	page
7. A new multimoment method to obtain solutions of the boundary layer equations	58
7.1. Introductory remarks	58
7.2. The modified Crocco equation	59
7.3. A special choice for δ	63
7.4. The polynomial approximation for S and compatibility conditions of the modified Crocco equation	65
7.5. Moments of the modified Crocco equation	68
7.6. Summary of the formulae to be used in the new calculation method	69
7.7. Step by step solution starting from given initial conditions	71
7.8. Similar solutions for $\bar{U} = \bar{x}^{\lambda_1}$	74
7.9. Series solutions for special types of the functions $U(x)$ and $v_0(x)$	78
7.9.1. General remarks	78
7.9.2. Series expressions for some functions occurring in the theory	80
7.9.3. The zero-order terms of the series solutions	82
7.9.4. The terms of order $p > 0$ of the series solution	83
7.9.5. Comparison of the new series method with existing series methods	85
7.10. Calculation of some characteristic boundary layer parameters from the coefficients a_n	86
7.11. Some related methods known from the literature	87
8. Some applications of the new calculation methods	89
8.1. Introductory remarks	89
8.2. The flat plate without suction	89
8.3. The plane stagnation point without suction	90
8.4. Hartree's boundary layers without suction	91
8.5. The flat plate with $v_0 \sim x^{-\frac{1}{2}}$	91
8.6. The plane stagnation point with constant suction velocity	92

	page
8.7. Howarth' boundary layer flow for $\bar{U} = 1 - \bar{x}$	
without suction	92
8.7.1. General	92
8.7.2. The momentum method	93
8.7.3. The multimoment method	94
8.8. Tani's boundary layers for $\bar{U} = 1 - \bar{x}^j$	95
8.9. The boundary layer on a circular cylinder without suction: $\bar{U} = \sin \bar{x}$	96
8.9.1. General	96
8.9.2. The momentum method	97
8.9.3. The multimoment method	97
8.10. Curle's boundary layer flow for $\bar{U} = \bar{x} - \bar{x}^3$	99
8.10.1. General	99
8.10.2. The momentum method	99
8.10.3. The multimoment method	99
8.11. Iglisch' solution for the flat plate with constant suction velocity	100
8.11.1. General	100
8.11.2. The momentum method	100
8.11.3. The multimoment method	101
8.12. Rheinboldt's boundary layer on a flat plate with discontinuous suction	103
8.12.1. General	103
8.12.2. The momentum method	103
8.12.3. The multimoment method	105
8.13. Schubauer's elliptic cylinder	105
8.13.1. General	105
8.13.2. Results of boundary layer calculations	106
8.14. Concluding remarks on the new calculation methods	108
9. Stability and transition	110
9.1. Introductory remarks	110
9.2. Principles of linear stability theory	112
9.2.1. General	112
9.2.2. The Orr-Sommerfeld equation	112
9.2.3. The stability diagram	115

	page
9.2.4. The amplification factor	116
9.3. Some available stability diagrams	118
9.4. Lin's formulae for the critical Reynolds number	120
9.5. Reduction of Pretsch's results to a form suitable for use on a digital computer	122
9.6. Some existing methods for the calculation of the transition point	123
9.7. A new method for the semi-empirical determination of the transition region	124
9.7.1. General	124
9.7.2. The amplification factor for the flat plate without suction	125
9.7.3. The amplification factor for the EC 1440 airfoil section without suction	126
9.7.4. The amplification factor for boundary layers with suction through a porous surface	128
9.8. Some results for the flat plate with different suction laws	129
9.8.1. The flat plate with constant suction velocity	129
9.8.2. The flat plate with varying suction velocity	131
10. Experimental investigation of the laminar boundary layer on an impervious 28 ^o thick airfoil section	133
10.1. Introductory remarks	133
10.2. Description of the experimental apparatus	134
10.2.1. The wind tunnel	134
10.2.2. The model	134
10.2.3. Hot-wire equipment	135
10.2.4. Other apparatus	135
10.3. Test methods and reduction of data	135
10.3.1. Pressure distribution measurements	135
10.3.2. Hot-wire measurements	136
10.3.3. Determination of the position of the hot-wire relative to the wall	137

	page
10.3.4. Measurements with the surface tubes	138
10.3.5. Flow visualisation experiments	138
10.4. Results of the experiments	139
10.4.1. The pressure distribution	139
10.4.2. Results of the boundary layer measurements	141
10.4.3. Results of the flow visualisation experiments	142
10.5. Boundary layer calculations using the measured pressure distribution	143
10.5.1. The momentum method	143
10.5.2. The multimoment method	145
10.6. Concluding remarks on the experiments without suction	146
11. Experimental investigation of a 15° thick laminar flow airfoil section with distributed suction	147
11.1. Introductory remarks	147
11.2. Description of the experimental apparatus	148
11.2.1. General	148
11.2.2. The model	148
11.2.3. Boundary layer traversing apparatus	150
11.2.4. Instruments for transition detection	151
11.2.5. Other equipment	151
11.3. Test methods and reduction of data	151
11.3.1. General	151
11.3.2. The pressure distribution and free stream speed	152
11.3.3. Determination of the suction distribution and suction drag coefficient	152
11.3.4. Determination of the wake drag	155
11.4. Results of the pressure distribution measurements	157
11.5. Results of boundary layer surveys on the upper surface with and without suction	158
11.6. Transition and drag of the unsucked airfoil	161
11.6.1. General	161
11.6.2. Transition and drag for the upper surface at $\alpha = 0^\circ$ without suction	162

	page
11.6.3. Transition and drag for the upper surface at $\alpha = 3^\circ$ without suction	162
11.7. Transition and drag with suction at $\alpha = 0^\circ$	164
11.7.1. General	164
11.7.2. Transition and drag with suction; series 1	165
11.7.3. Transition and drag with suction; series 2	167
11.7.4. Transition and drag with suction; series 3	167
11.7.5. Transition and drag with suction; $\alpha = 0$ upper surface only; filtering paper covered with nylon; series 4-7	167
11.7.6. Summary of the comparisons between the measured and calculated transition positions	169
11.8. Summary of the drag coefficients obtained with and without suction	170
11.9. Concluding remarks on the experiments with suction	170
12. Conclusions	172
13. References	174
14. Overzicht (Summary in Dutch)	183
15. Appendix 1: The drag of a flat plate with suction	187
Tables	
Figures	

List of symbols.

Symbols which are used only locally are defined in the text; other symbols are listed below.

a	coefficient in eq. (4.1)
a	scaling factor for y; in chapter 5 only; numerical value 1.3
a ₁	constant in equations (4.13) and (5.39)
a _n	coefficient in polynomial expression (7.29)
a ₀	$\left(\frac{\tau_o x}{\mu U}\right)^2 \left(\frac{Ux}{\nu}\right)^{-1} = \tau_o^2$
a _{n,p}	coefficients in series expansion (7.92) for a _n
Δa_n	increment of a _n ; equation (7.70)
δa_n	increment of a _n ; section 7.8
\bar{a}_n	starting value for a _n in sections 7.7 and 7.8
a _n *	defined by equation (8.1)
A	integration constant in chapter 6
A _{ij}	elements of inverse matrix in chapter 7
b	coefficient in equation (4.1)
b	scaling factor for y; in chapter 5 only; numerical value 0.3
b	spanwise extent of porous surface in chapter 11 (0.805 m)
b ₁	constant in equations (4.13) and (5.39)
c	coefficient in equation (4.1)
c	reference length, equal to chord length for airfoil sections
\bar{c}	$c_r + i c_i = \frac{\bar{\beta}}{\bar{\alpha}} = \frac{\beta_r}{\alpha} + i \frac{\beta_i}{\alpha}$; equation (9.6)
c _{d_f}	friction drag coefficient of flat plate defined by equation (3.18)
c _{d_s}	suction drag coefficient
c _{d_t}	total drag coefficient
c _{d_w}	wake drag coefficient
c _p	pressure loss coefficient $\frac{\Delta p}{\frac{1}{2} \rho U_\infty^2}$

c_q	suction flow coefficient $\frac{Q}{U_\infty c}$
c_{q_i}	suction flow coefficient for compartment number i in chapter 11
c_{q_u}	suction flow coefficient for the upper surface
c_{q_l}	suction flow coefficient for the lower surface
d	coefficient in equation (4.1)
d	length scale in Lin's formulae (9.19) and (9.20)
D	dissipation integral defined by equation (2.23)
$2D^*$	$2 \int_0^{\infty} \left(\frac{\partial u/U}{\partial y/\theta} \right)^2 d \frac{y}{\theta}$; nondimensional dissipation integral
e_{i_n}	$\frac{\partial E_i}{\partial a_n}$ defined by equation (7.76)
E_i	defined by equation (7.74)
\bar{E}_i	starting value for E_i in section (7.8)
f	number denoting value of reduced frequency $\frac{\beta_r \nu}{U}$ in table 9.4
f	exponent in equation (7.79); used in chapter 7 and 8 only
$f(\eta)$	nondimensional streamfunction: for chapter 3 defined by eq. (3.6)
$f(\eta)$	nondimensional streamfunction: for chapter 6 defined by eq. (6.8)
$f_1(\eta), f_2(\eta), f_3(\eta)$	defined by equations 5.6-5.9 in chapter 5
f_1, f_3, f_5, \dots	defined by equation (3.25)
$F_{2n+1}(\eta)$	defined by eq. (3.24)
$F(\xi, \eta)$	nondimensional streamfunction in Görtler's series method; defined by eq. (3.29)
$F_0, F_{\frac{1}{2}}, F_1, \dots$	Görtler's universal functions in section 3.2.4.
$F(\eta)$	defined by eq. (4.9) in chapter 4
$F(\mathcal{L}_1)$	Pohlhausen's universal function defined by equation (4.12) in chapter 4

$F_1(\eta)$	
$F_2(\eta)$	defined by equations 5.3-5.9 in chapter 5
$F_3(\eta)$	
$G(\eta)$	defined by equation (4.10) in chapter 4
H	$\frac{\delta^*}{\theta}$
\bar{H}	$\frac{\epsilon}{\theta}$
$J_{k,n}$	defined by eq. (7.55)
J_k	defined by eq. (7.52)
$J_{k,p}$	defined by eq. (7.98) and (7.99)
k	0,1,2,...K
K	N-5 in chapter 7
K	shape factor in chapter 5
K_1, K_2	constants in equation (9.25)
l	$\left(\frac{\partial u/U}{\partial y/\theta} \right)_o = \frac{\tau_o \theta}{\mu U}$
l_1	$\frac{\sigma^2}{\nu} \frac{dU}{dx} = \frac{-2}{\sigma^2} \frac{d\bar{U}}{dx}$
l_2	$\frac{-v_o \sigma}{\nu} = \bar{v}_o \bar{\sigma}$
L	shape factor in chapter 5
m	$\left(\frac{\partial^2 u/U}{\partial (y/\theta)^2} \right)_o$
m_1	constant in equation 3.1
M	$2\ell - 2(2+H)\Lambda_1 - 2\Lambda_2$
M_k	defined by equation (7.51)
$M_{k,p}$	defined by equation (7.98)-(7.99)
N	degree of polynomial expression (7.29)
p	static pressure in chapter 2 and 9
p	order of series expansion in chapter 7 and 8
p'	fluctuation of static pressure in chapter 9
p^*	$p + p'$ in chapter 9

XIII

p_t	free stream total pressure in chapters 10 and 11
p_1, p_2, \dots, p_9	coefficients in eq. (5.10)-(5.12)
p_x	static pressure on body surface at distance x from the stagnation point
$p_{k,n}$	defined by equation (7.55)
p_k	defined by equation (7.53)
$p_{k,p}$	defined by eqns. (7.98)-(7.99)
p_{w+}	static pressures at side wall of wind tunnel (see fig.11.1)
p_{w-}	
Q	suction flow per unit span $m^3 \text{sec}^{-1} m^{-1}$
$q_{k,l,n}$	defined by equation (7.55)
Q_k	defined by equation (7.54)
$Q_{k,p}$	defined by equation (7.98)-(7.99)
r_p	defined by equations (7.94) and (7.96)
R	radius of cylinder in section 8.9
R_{δ^*}	$\frac{U\delta^*}{\nu}$
R_{θ}	$\frac{U\theta}{\nu}$
R_c	$\frac{U_o c}{\nu}$
S	$\frac{-2}{t}$
s	distance along contour of airfoil section, measured from leading edge (chapter 11 only)
\bar{s}	s/c
t	time
t_n	δa_n in section 7.8.
T	amplification rate of unstable disturbances defined by equation (9.17)
T_o	constant in eq. (9.25)
u	velocity component parallel to wall
u'	fluctuation of u
u^*	$u+u'$ in chapter 9
\bar{u}	u/U in general; $u/ U $ in chapter 6

\bar{u}_p	velocity measured by surface tubes; chapter 10
U	velocity component parallel to wall at edge of boundary layer
\bar{U}	U/U_∞
U_∞	reference speed, equal to free stream speed in chapters 10 and 11
v	velocity component normal to wall
v'	fluctuation of v in chapter 9
v^*	$v+v'$ in chapter 9
v_o	normal velocity at surface; negative for suction
$\frac{\bar{v}_o}{U_\infty}$	$-\frac{v_o}{U_\infty} \sqrt{\frac{U_\infty c}{\nu}}$
V	wind speed in section 8.9
x	distance along wall measured from stagnation point, (fig. 2.1)
x_p	distance along chord of airfoil section (fig. 2.1)
$\frac{\bar{x}}{c}$	x/c
y	distance normal to wall
y_p	ordinate of airfoil section
y_r	distance from reference position outside boundary layer (chapter 10)
$\frac{\bar{y}}{\delta}$	$\frac{y}{\delta} = \frac{y}{x} \sqrt{\frac{Ux}{\nu}}$
z	new variable, defined by eq. (7.79)
z_p	spanwise coordinate, chapter 10
α	angle of attack of airfoil section
α_1	$\bar{U} \delta^2$ in chapter 7
$\bar{\alpha}$	$\frac{2\pi}{\lambda}$ in chapter 9 only
β	Hartree parameter defined by eq. (3.4)
$\beta_1, \beta_2, \beta_3, \dots$	defined by eq. (7.68)
$\beta(\xi)$	Görtler's function defined by eq. (3.31)
$\bar{\beta}$	$\beta_r + i\beta_i$ in section 9.2.2.

β_o	$\frac{2m_1}{m_1+1}$ (eq. 3.36)
γ	$1-3\lambda_1$
δ	measure for boundary layer thickness in general
δ	defined by $\frac{\delta}{x} \sqrt{\frac{Ux}{\nu}} = 1$ in chapter 7 and further
$\bar{\delta}$	$\frac{\delta}{c} \sqrt{\frac{U_\infty c}{\nu}}$
δ^*	displacement thickness $\int_0^{\delta} (1-\bar{u}) dy$
$\bar{\delta}^*$	$\frac{\delta^*}{c} \sqrt{\frac{U_\infty c}{\nu}}$
δ_{k+2}	defined by eq. (2.26)
ϵ	energy loss thickness $\int_0^{\epsilon} \bar{u}(1-\bar{u}^2) dy$
η	$y \sqrt{\frac{m_1+1}{2}} \frac{U}{\nu x}$ in section 3.12
η	$y \sqrt{\frac{u_1}{\nu c}}$ in section 3.2.2.
η	defined by eq. (3.28) in section (3.2.4)
η	$\frac{y}{\delta}$ in chapter 4
η	$\frac{y}{\sigma}$ in chapter 5
η	$\frac{y}{x} \sqrt{\frac{ u_1 }{\nu}} = \frac{y}{x} \sqrt{\frac{ U }{\nu}}$ in chapter 6
η_1	$-\lambda \eta$ in chapter 6
θ	momentum loss thickness $\int_0^{\theta} \bar{u}(1-\bar{u}) dy$
$\bar{\theta}$	$\frac{\theta}{c} \sqrt{\frac{U_\infty c}{\nu}}$
λ	$\frac{v_o x}{\sqrt{\nu u_1 }}$ in chapter 6
λ	$\frac{\delta^2}{\nu} \frac{dU}{dx}$ in chapter 4
λ	wave length of disturbance in chapter 9
λ_1	$\frac{x}{U} \frac{dU}{dx} = \frac{\bar{x}}{\bar{U}} \frac{d\bar{U}}{d\bar{x}} = \bar{\delta}^2 \frac{d\bar{U}}{d\bar{x}}$

λ_2	$\frac{-v_o}{U} \sqrt{\frac{Ux}{\nu}} = \frac{-v_o}{v_o} \bar{\delta} = \frac{-v_o \delta}{\nu}$
$\lambda_{1,p}$	coefficients in eq. (7.80)
$\lambda_{2,p}$	coefficients in eq. (7.81)
Λ_1	$\frac{\theta^2}{\nu} \frac{dU}{dx} = \bar{\theta}^2 \frac{d\bar{U}}{d\bar{x}} = \ell_1 \left(\frac{\theta}{\sigma}\right)^2$
Λ_2	$\frac{-v_o \theta}{\nu} = \frac{-v_o}{v_o} \bar{\theta} = \ell_2 \frac{\theta}{\sigma}$
μ	coefficient of dynamic viscosity
ν	$\frac{\mu}{\rho}$ coefficient of kinematic viscosity
ξ	Görtler's variable defined by equation (3.27)
ρ	density
σ	measure for boundary layer thickness in chapter 5
$\bar{\sigma}$	$\frac{\sigma}{c} \sqrt{\frac{U_{\infty} c}{\nu}}$
σ_a	amplification factor defined by eq. (9.16)
$(\sigma_a)_{\max}$	maximum value of σ_a at a certain position
σ_p	defined by equations (7.96) and (7.97)
τ	$\mu \frac{\partial u}{\partial y}$ shear stress
$\bar{\tau}$	$\frac{d\bar{u}}{d\bar{\eta}}$ in chapter 6
$\bar{\tau}$	$\frac{\partial \bar{u}}{\partial \bar{y}} = \frac{\tau \delta}{\mu U}$ in chapter 7 and 8
τ_o	wall shear stress
$\bar{\tau}_o$	$\frac{\tau_o \delta}{\mu U} = \sqrt{a_o}$ in chapter 7 and further
$\Phi(y)$	$\Phi_r + i\Phi_i$, amplitude function in equation (9.4)
Ψ	stream function in chapter 3 and 6
ψ	$\psi_r + i\psi_i$ stream function of disturbance defined by equation (9.4)

subscripts

i	at the instability point
o	at the surface
sep	at the separation point
st	at the stagnation point
tr	at transition
te	at trailing edge
le	at leading edge

primes denote differentiation with respect to η in chapter 3 and 6 and to \bar{u} in chapter 7. They denote fluctuation components in chapter 9.