

Erratum to: The toughness of epoxy polymers and fibre composites modified with rubber microparticles and silica nanoparticles

T. H. Hsieh · A. J. Kinloch · K. Masania ·
J. Sohn Lee · A. C. Taylor · S. Sprenger

Published online: 4 March 2011
© Springer Science+Business Media, LLC 2011

Erratum to: J Mater Sci (2010) 45:1193–1210
DOI 10.1007/s10853-009-4064-9

The original version of this article unfortunately contained an error in equation 13 on page 1207. Equation 13 should read:

$$F'(r_y) = r_y \left[\left(\frac{4\pi}{3V_f} \right)^{\frac{1}{3}} \left(1 - \frac{r_p}{r_y} \right)^3 - \left(\frac{8}{5} \right) \left(1 - \frac{r_p}{r_y} \right) \right. \\ \left. \times \left(\frac{r_p}{r_y} \right)^{\frac{5}{2}} - \left(\frac{16}{35} \right) \left(\frac{r_p}{r_y} \right)^{\frac{7}{2}} - 2 \left(1 - \frac{r_p}{r_y} \right)^2 + \left(\frac{16}{35} \right) \right].$$

The online version of the original article can be found under doi:[10.1007/s10853-009-4064-9](https://doi.org/10.1007/s10853-009-4064-9).

T. H. Hsieh · A. J. Kinloch (✉) · K. Masania · J. Sohn Lee ·
A. C. Taylor (✉)
Department of Mechanical Engineering, Imperial College
London, South Kensington Campus, London SW7 2AZ, UK
e-mail: a.kinloch@imperial.ac.uk

A. C. Taylor
e-mail: a.c.taylor@imperial.ac.uk

S. Sprenger
Nanoresins AG, Charlottenburger Strasse 9, 21502 Geesthacht,
Germany